

LIST OF FIGURES

FIGURE		PAGE
1	Cell polarizations as a function of operating current.....	7
2	Electrochemical operation of a cell (discharge).....	12
3	Optical microscopy (a) and SEM (b-c) images of Cu-16%Zn-6.5% Al alloy after annealing at 850°C for 3 h and quenched at 100°C and subsequently at 0°C into water. Alloy structure revealed after etching with an alcoholic ferric chloride solution. XRD pattern of quenched Cu-16%Zn-6.5%Al alloy evidencing the martensitic structure.....	14
4	Peak current densities versus scan rate and peak potentials versus scan rate.....	15
5	XRD pattern of the AZ91D magnesium alloy treated in the Zn ²⁺ /Al ³⁺ solution at applied potential of -1.7 V.....	16
6	Nyquist plots of the electrochemical impedance response (a), and Bode plots of Z vs. frequency (b) of uncoated and Zn-Al LDHs coated AZ91D alloy in 3.5 wt.% NaCl solution.....	16
7	Polarization curves at a scan rate of $v = 1 \text{ mV s}^{-1}$ and 25 °C in a 4 mol KOH solution for Al2000 Clad, Al2000 and Al7000 anodes and NiOOH and air cathodes.....	17
8	Batteries for electric drive vehicles.....	18
9	Model of the one-dimension single-cell Zn-air battery.....	19
10	Potentio-dynamic polarization curves of prepared specimens.....	19

LIST OF FIGURES (Continue)

FIGURE		PAGE
11	EIS spectra for prepared Zn–Al–Mg alloys in 3.5 wt.% NaCl solution: (a) Nyquist diagrams; (b) Bode phase diagrams.....	20
12	Potentiodynamic polarization curves of 7A09-T6 alloy immersed in 3.5% NaCl solution as function of immersion time.....	21
13	Evolution of electrochemical parameters: (a) Open circuit potential (OCP); (b) Low frequency capacitance; (c) R_{ct} and R_f values for 7A09-T6 alloy samples in 3.5% NaCl solution as function of immersion Time.....	21
14	Schematic of the setup used for electrophosphating treatment.....	22
15	SEM micrograph of Zn–Ni electrophosphate coating obtained by the cathodic electrochemical method at different current densities A) 5, B) 15, C) 25, D) 35 mA/cm ²	23
16	Potentiodynamic polarization behavior of No.1 ~ No.9 Experimental Alloys.....	24
17	Galvanostatic discharge behavior of No.1~ No.9 experimental alloys.(a) Galvanostatic discharge behavior at 150 mA•cm ⁻² , (b) galvanostatic discharge behavior at 350 mA•cm ⁻²	24
18	X-ray diffraction (XRD) patterns of Mg-Li-Al-Ce-Y (a) and Mg-Li-Al-Ce-Y- Zn (b) alloys.....	25
19	Galvanostatic potential-time curves of pure magnesium, AZ31, Mg-Li-Al-Ce-Y, and Mg-Li-Al-Ce-Y-Zn alloys in 3.5 wt.% NaCl solution at 10 mA•cm ⁻² (a) and 180 mA•cm ⁻² (b).....	25

LIST OF FIGURES (Continue)

FIGURE		PAGE
20	Electrochemical impedance spectra (EIS) of pure magnesium, AZ31, Mg-Li-Al-Ce-Y, and Mg-Li-Al-Ce-Y-Zn alloys in 3.5 wt.% NaCl solution: (a) Nyquist plots, (b) Bode plots of impedance modulus vs. frequency, and (d) Bode plots of phase (c) anglesvs. Frequency.....	26
21	Galvanodynamic polarization curves of the anode (1) and the Cathode (2), current-voltage curve (3), and power curve (4) of AA cell with 8 mol NaOH p 0.015 M Na ₂ SnO ₃ • 3H ₂ O at 60 °C.....	30
22	Schematic (a) and photograph (b) of AA ECG.....	27
23	Potentiodynamic polarization plots for the corrosionof Mg–Al–Zn–Mn alloy in 30% aqueous ethylene glycolcontaining different concentrations of the chloride ions at 50 °C.....	28
24	SEM images of anode electrodes after 60 min immersion test in 4 mol NaOH; (a) 4N Al anode, (b) Al-Zn anode, (c) Al-Zn-In anode.....	30
25	I-V and I-P curves of three anodes for the full-cell in 4M NaOH; (a) 4N Al, (b) Al-Zn, (c) Al-Zn-In.....	30
26	Discharge behavior of anodes at different discharge voltages; (a) 1.2 V, (b) 1.0 V, (c) 0.8 V.....	31
27	SEM images of investigated alloys: (a) AZ63 alloy; (b) details of the microstructure framed in (a); (c) AZI alloy; and (d) AZIT alloy and its partial enlargement.....	32

LIST OF FIGURES (Continue)

FIGURE	PAGE
28 Performance of Mg-CuCl seawater-activated cell with AZ63, AZI and AZIT anodes in 3.5 wt.%NaCl at ambient temperature: Plots of current density vs. cell voltage (a) and plots of current density vs. power density (b).....	32
29 Cyclic voltammograms in deaerated boric acid buffer (pH 6.5) and boratebuffer (pH 8.4). a) Boric acid buffer cycle 1, b) boric acid buffer cycle 3, c) boratebuffer cycle 3. Scan rate 10 mV/s. Samples were held at 1.4 V _{MMSE} for 10 min prior to initial scan.....	34
30 Measured potential plotted against applied current during anodic dissolution stage of AESEC measurements in artificial perspiration.....	34
31 SEM images of the microstructure of nanoporous Ag-Cu derived from dealloyed Mg ₆₅ Ag _{12.5} Cu _{12.5} Y ₁₀ metallic glass in 0.04 mol H ₂ SO ₄ aqueous solution for different immersion times: (a) 5 min; (b) 10 min; (c) 30 min; (d) 50 min; (e) 60 min; (f) 70 min; (g) 80 min; (h) 90 min.....	35
32 Reaction interface between the corrosion layer and the metallic glass matrix after dealloying Mg ₆₅ Ag _{12.5} Cu _{12.5} Y ₁₀ glassy precursor for 5 min: (a) cross-section SEM image and (b) linear composition profile across the reaction interface. Influence of immersion time (t) on the thicknesses (T) of the nanoporous Ag-Cu layer and the glass matrix in free-corrosion conditions: plots on (c) normal scale and (d) logarithmic scale for measurement of the growth exponent (n) The standard deviation of the measured thickness is provided as the error bar in the plot.....	36

LIST OF FIGURES (Continued)

FIGURE		PAGE
33	Vacuum heated pressing furnace.....	38
34	Isomet Low Speed Saw.....	39
35	Grinder-Polisher.....	39
36	The parallel reflecting planes of crystal lattice, path difference of two reflected wave (red lines).....	41
37	X-Ray Diffractometer.....	42
38	Picotest multimeter.....	43
39	Hardness Tester.....	44
40	Density Kit.....	45
41	Diagram of the scanning electron microscope technique.....	46
42	Scanning Electron Microscopy.....	46
43	Potentiostat 466.....	47
44	Cyclic Voltammetry technique (model Potentiostat 466).....	48
45	Discharging measurement (a) measured voltage and current of Cu anode/Al cathode dip in NaCl+DI water for 40 min by Picotest digital multimeter (b) program setup/run logging worksheet by M35XX Excel Add-In program to evaluate the electrical power.....	49
46	Al-Zn alloy cathode and Cu anode.....	50
47	X-ray diffraction patterns of Cu anode.....	51
48	X-ray diffraction patterns of Al cathode.....	52
49	X-ray diffraction patterns of Al and alloy Al-Zn (1-5 wt%).....	53
50	The resistance of pure Cu, Al and alloy of Al-Zn (1-5 wt%).....	54
51	The microhardness of pure Cu, Al and alloy of Al-Zn (1-5 wt%).....	55
52	The density of pure Cu, Al and alloy of Al-Zn (1-5 wt%).....	56
53	The SEM images of pure Cu, Al and alloy of Al-Zn (1-5 wt%) before dip in NaCl+ DI water solution.....	57
54	The SEM images of pure Cu, Al and alloy of Al-Zn (1-5 wt%) after dip in NaCl+ DI water solution.....	58

LIST OF FIGURES (Continue)

FIGURE		PAGE
55	Volammetric behavior of Cathode Al+Zn and anode Cu for 100 Cyclic Voltammetry technique.....	58
56	Relationship time with electric potential after dip Cathode Al, Al-Zn and anode Cu in aqueous NaCl.....	61
57	Relationship time with electric current after dip Cathode Al, Al-Zn and anode Cu in aqueous NaCl.....	62
58	Relationship time with electric power after dip Cathode Al-Zn and anode Cu in aqueous NaCl.....	63
59	Electrochemical battery fabricated 4 cells.....	64
60	Electrochemical battery fabricated 4 cells and applied turn on a LED lamp.....	64
61	Discharging of electrochemical cell.....	65

มหาวิทยาลัยมหาสารคาม